

# SIDEWALK CAFÉ REQUIREMENTS

## Sidewalk Café

1. Must comply with 4301 Division of Liquor Control
2. Must comply with 3794.01 Smoking Ban Law
3. Must comply with 2010 ADA requirements

## Site Plan Requirements

- Location and dimensions of the sidewalk café
- Location of all entrance/ exits to sidewalk café and establishment
- Cafés may not obstruct emergency exits or fire standpipes
- Fencing must have a minimum clearance of six feet (6') from the back of curb, three feet (3') from all right-of-way objects.
- Fencing must have a minimum clearance of five feet (5') in all areas considered turning points for ADA accessibility (e.g. establishment entrance, café entrance, intersecting isles); entrances must be a minimum of three feet (3') and a maximum of five feet (5')
- All clearance measurements inside the café are taken from when patrons are seated
- Note the location and distance to all right-of-way objects (e.g. street lights, street trees, mail boxes, catch basins, curb)
- Show all tables and chairs as to how they will be arranged with in the sidewalk café
- Show location of ADA accessible seating; five percent( 5%) or a minimum of one (1) table
- All seating may not consist of “high” or “bar stool” height tables and chairs.
- Show location of all other equipments that will be located with in the sidewalk café

## Fence Requirements

- Must be made of metal
- Must run continuous and uninterrupted
- Chains and ropes are not acceptable fencing materials
- Height must be a minimum of thirty six inches (36”) and a maximum forty two inches (42”)
- Lower rail must be a minimum of four inches (4”) off of the sidewalk
- Spindles must not exceed four inch (4”) spacing
- Pointed or sharp finishes on posts, rails, or spindles are not acceptable
- Must maintain a minimum of fifty percent (50%) visibility (Ability to see through the fence)
- Core drilling and setting posts will not be permitted (See Standard Drawing for preferred method)

## Awning Requirements

- Must meet Ohio Building Code requirements (Obtain separate permit from Summit County Department of Building Standards 330-630-7280)
- Can not over hang past the sidewalk café area
- Must maintain a minimum of eighty-five percent (85%) visibility
- Enclosures, side flaps, or temporary/permanent banners are not allowed